

HENUORTH TRUCK

SPECIFICATIONS KENWORTH 953 TRUCK

Engine	
♦ Make	Cummins
♦ Model	NTA 400
♦ Fuel Supply	Rotary Pump Diesel
♦ Max Gross Рошег	Hp @ 2200 Rpm 400
♦ Max Gross Torque	NH

GENERAL	
 Basic Vehicle 	6x6 Tractor Heavy Hauler
Configuration	Forward Facing Cab over Chassis Tractor
♦ Gross Vehicle Weight	Kg 45351
◆ Curb Weight	Kg 20230
◆ Payload	Kg 25121
♦ Wheel Base	mm 7110
◆ Length	mm 9701
♦ Width	mm 3390
♦ Height	mm 3740
Ground Clearance	mm 500
Max Speed on roads	Km/H 60
♦ Crew and Passenger	2
Suspension Front	Leaf Springs With Telescopic Dampers
Suspension Rear	Double Axle Bogey
Number of Driven Wheels	6
Power Steering	Standard

Transmission Axles & Wheels	
♦ Transmission Make And Model	Allison TG-637
♦ Transmission Selection	Automatic
♦ Transfer Case Make And Model	FABCO TC110
♦ Transfer Case Selection	Manual
♦ Front Axle	Clark FDS 22600
	Steered rigid Axle
♦ Rear Axle	Clark BD100000
	Double Rigid axles
♦ Wheels	445/65R22.5

HULL	
◆ Configuration	Single Cab over engine

STANDARD EQUIPMENT

- ♦ PTO
- Air Conditioned



Head Office: Al-Ahsa Street P.O.Box 27021, Riyadh 11417, T: + 966 11 2148078 F: + 966 11 4760989 E: eraf@eraf.com | www.eraf.com