

ERAF

شركة إيراف الصناعية المحدودة
ERAF Industrial Company Ltd.



AL BATTAR TACTICA

www.eraf.com

SPECIFICATIONS

AL BATTAR

TACTICA

GENERAL

◆ Basic Vehicle	Forward Facing Boxed Construction
◆ Configuration	Constant 4x4 Troop Carrier
◆ Gross Vehicle Weight	11,600Kg
◆ Curb Weight	15,100Kg
◆ Payload	3,500Kg
◆ Wheel Base	2780 mm
◆ Length	5800 mm
◆ Width	2580 mm
◆ Height	2580 mm
◆ Ground Clearance	360 mm
◆ Max Speed on roads	100 Km/h
◆ Crew and Passenger	2+10
◆ Suspension Front	Twin Parabolic Leaf Spring With Telescopic Dampers
◆ Suspension Rear	Multi Parabolic Leaf Spring With Telescopic Dampers
◆ Number of Driven Wheels	4
◆ Power Steering	Standard

Transmission Axles & Wheels

◆ Transmission Make And Model	Allison 2500 SP
◆ Transmission Selection	Automatic 6 Speed
◆ Transfer Case Make And Model	DGS TCA850 (Two Shaft)
◆ Transfer Case Selection	Pneumatic Selection with Diff Lock
◆ Front Axle	Mercedes AL5 Steered Rigid Axle Hypoid Driven With Differential Lock
◆ Rear Axle	Mercedes AM4 Rigid Axle Hypoid Driven With Differential Lock
◆ Wheels	385/60R22.5, Steel rims , fitted with RFI

HULL

◆ Configuration	Monocoque box shaped hull with cab over engine design. Dual Layer Spaced Armor Protected up to BS EN 1522 FB7
-----------------	--

STANDARD EQUIPMENT

◆ 200l Protected Fuel Tank
◆ Escape Hatch
◆ 7 Gun ports
◆ Provision for BAE ROW
◆ Safari Roof
◆ Cruise Control
◆ HD Air Conditioning System
◆ ABS Brakes

Engine

◆ Make	Mercedes
◆ Model	OM 926 LA Euro III
◆ Fuel Supply	Common Rail Diesel Injection
◆ Max Gross Power	302 HP(225 kW) @ 2,200 rpm
◆ Max Gross Torque	1,200 Nm @ 1,200 rpm - 1,600 rpm

Accessories

◆ GPS System
◆ Auxiliary Alternator for ancillaries
◆ First Aid Kit
◆ Hydraulic Jack And Vehicle Tools